

# T700 AIR PORTABLE TRAMP OIL REMOVAL UNIT

- POWERED BY COMPRESSED AIR
- REMOVES TRAMPOIL CONTAMINATION
- EXTENDS COOLANT LIFE
- REDUCES COOLANT COSTS –
   REDUCED CONSUMPTION AND REDUCED DISPOSAL VOLUMES
- INCREASED MACHINE TOOL EFFICIENCY / PRODUCTIVITY
- REDUCES BACTERIAL GROWTH
- IMPROVED OPERATOR CONDITIONS - IMPROVED HEALTH AND SAFETY
- MINIMAL RUNNING COSTS
- ONE UNIT CAN SERVICE AN ENTIRE WORKSHOP






# **T700 AIR - PORTABLE TRAMP OIL REMOVAL UNIT**

### **DIMENSIONS**

# 1306mm



### **COOLANT SAMPLES**



### **FEATURES**

- PORTABLE STAINLESS STEEL CONSTRUCTION
- MINIMAL SERVICING REQUIRED -NO CONSUMABLE PARTS
- REUSABLE BAG FILTER
- ONE UNIT CAN SERVICE AN ENTIRE WORKSHOP
- UNATTENDED OPERATION
- EASY TO USE MINIMAL SETUP AND NO "LEVELLING" REQUIRED
- UNIVERSAL APPLICATION WORKS ON ANY COOLANT SUMP

## **RESULTS**

- REMOVES TRAMP OIL CONTAMINATION
- EXTENDS COOLANT LIFE
- REDUCES COOLANT COSTS REDUCED CONSUMPTION AND REDUCED DISPOSAL VOLUMES
- INCREASED MACHINE TOOL EFFICIENCY / PRODUCTIVITY
- REDUCES BACTERIAL GROWTH
- IMPROVED OPERATOR CONDITIONS -IMPROVED HEALTH AND SAFETY

### **TECHNICAL SPECIFICATIONS**

FLUID FLOW RATE (L/M) 12 L/M

POWER	AIR OPERATED		
DIMENSIONS (MM)	H: 1306	W: 599	L: 847
WEIGHT (KG)	100 KG		
CONNECTIONS	INLET - 3/4" LANCE	OUTLET - 3/4" LANC	E

### ETL FLUID EXPERTS LTD

GRIMBALD CRAG ROAD, KNARESBOROUGH NORTH YORKSHIRE, HG5 8PY

T +44 (0)1423 522911 E SALES@ETLFE.COM

WWW.ETLFLUIDEXPERTS.COM

